

CLAIMS

What is claimed is:

- 5
- Sub A27
1. A pedestal defined zero throat write head comprising:
a first pole having a pedestal, the pedestal having a front, a back, a top and a bottom,
the back of the pedestal having a recess therein, the recess running from the top of the
pedestal to the bottom of the pedestal;
a second pole;
a gap separating the pedestal of the first pole from a portion of the second pole.
 2. The pedestal defined zero throat write head of claim 1 wherein the recess
includes a first edge and a second edge, the first edge and the second edge being directly
under a portion of the second pole.
 3. The pedestal defined zero throat write head of claim 1 wherein the recess
includes a first edge and a second edge, the first edge and the second edge being outside of
the second pole.
 - 20 4. The pedestal defined zero throat write head of claim 1 wherein the second
pole further includes a nose and wherein a portion of the pedestal is directly under the nose.
 5. The pedestal defined zero throat write head of claim 1 further comprising:
at least one coil between the first pole and the second pole.

6. A method for providing pedestal defined zero throat write head comprising

the steps of:

(a) providing a first pole having a pedestal, the pedestal having a front, a back, a top and a bottom, the back of the pedestal having a recess therein, the recess running from the top of the pedestal to the bottom of the pedestal;

(b) providing a gap above the pedestal;

(c) providing a second pole, the gap separating the pedestal from a portion of the second pole.

7. The method of claim 6 wherein the first pole providing step (a) further includes the steps of:

(a1) depositing the pedestal; and

(a2) removing a portion of the pedestal to provide the recess.

8. The method of claim 6 wherein the first pole providing step (a) further includes the step of:

(a1) providing the recess having a first edge and a second edge such that the first edge and the second edge are directly under a portion of the second pole.

9. The method of claim 6 wherein the first pole providing step (a) further includes the step of:

(a1) providing the recess having a first edge and a second edge such that the first edge and the second edge are outside of the second pole.

10. The method of claim 1 wherein the second pole providing step (c) further

includes the step of:

(c1) providing a nose such that a portion of the pedestal is directly under the nose.

11. The method of claim 6 further comprising the step of:

(d) providing at least one coil between the first pole and the second pole.

Sub A2
5
Cmcl.

10087505.030102